



a telephoné and onls called party collects The dialed digits TIVO sends a setup nessage to GCO The setup nessage to GCT - 340 Forward the set op nessage TIUT to If the destination address of the setup nessage matches TIUT, sending to the TIUs a setup acknowledgement newage retwork resources ~370 Send from TIUO to TIUT on end-to-end king missage Send from TIUT to TIUO on end-to-end Ringback nessage Upon call acceptance by the called party, send an end-to-end Connect nessage from TIUT to TIU





F161.5




Figure 6

ij

1: 5

ľŲ




Figure 7






Figure 8

3.

|.4

ii |. 4




Figure 9




Figure 10

Figure 11




Figure 12

ļ. ž

|- & |' ||




Figure 13




Figure 14

ŗħ

. 3

|: <u>a</u>




Figure 15




Figure 16







Figure 17

ļi ≢.










Figure 21





Figure 22






Figure 24




Figure 25




Figure 26




Figure 27




Figure 28




Figure 29








Figure 30







F16.33



send a riving threat ressage PRINT OF DRAWINGS AS ORIGINALLY F FD TTU. trom 11U+ to a redirect nessage from Send TIUT Verify, at GCT, call forwarding service subscription Detomine, at GC+, Forwarding number and billing information the GC redirect nessage from GCT to GC with billing information from GCo to TIUO a Call hold nessage Send 870 | Send a GC setup nessage from GCo to GCF GCT to GC setup acknowledgment nessage from GCF to GCo Gotemodity nessage GCo to NED Tronsfor nessage from GLo to TIU. °t processing the 5 Continue

FIG. 35

sage from TIUO to NEDOI PRINT OF DRAWINGS AS ORIGINALLY D after Truo sends a retip message to NEDO /~2000 and after TIV. receives a setup acknowledgment message Checks availability and reserves bi-directional capacity in the originating access networks Send a backbone reserve message from NED to a vouter within commiscation network After receiving the backbore reserve nessage at the router within communication retwork, whech - 2300 availability and reserve forward-direction capacity Forward the backbone reserve nessage from \ ~ 2400 the norter with the communication retwork At NEDO, receive a backbone reserve acknowledgment message from NEDT Sond a reserve acknowledgment message from NED to TIU